



TVOC[®]

Fixed PID monitor for volatile organic compounds.



Continuous detection of volatile organic compounds (VOCs) with multiple range from just one instrument.

Best available photoionisation (PID) detection

- PID independently verified as best performing on the market
- Range: 0-10, 0-100 or 0-1000 ppm from just one instrument
- In-built humidity resistance with no need to compensate
- Anti-contamination design for extended field operation
- Variable duty cycle prolongs run time
- Reliable diffusive monitoring - no pump required

Safety

- Accurate results over all environmental conditions
- Rugged and robust design withstands harsh environments
- Large LCD display for clear readings
- ATEX and IECEx approved

Ease of use

- Simple to use - minimal training required
- Easy access PID sensor for fast, simple servicing
- Simple calibration procedure
- Easily integrated into a control system

Low cost operation

- Inexpensive consumables and parts
- 2 year warranty when instrument registered online



TVOC is a fixed photoionisation detector (PID) for the continuous measurement of total volatile organic compounds (VOCs). TVOC accurately measures over three different detection ranges from just one instrument.

TVOC has a variable duty cycle set to 1 minute as standard. The user can adjust this to between 5 seconds and 5 minutes.

TVOC utilises a diffusive sample technique resulting in less contamination issues compared to pumped systems, reducing lamp cleaning and servicing requirements. The 4-20 mA analogue output enables TVOC to be integrated into a DCS control system to give warning or control of high VOC levels in the working environment.

ATEX approvals enable a 3 wire TVOC system to be used in Zone 2 hazardous areas, without safety barriers. ATEX and IECEx approvals allow TVOC to be used in Zone 1 hazardous areas, with safety barriers.

Simple to install, service and calibrate, TVOC requires no hot work permit and the PID sensor is accessible and changeable in a matter of seconds.

TVOC SystemPlus comes complete with a pumped sample system for applications where a sample needs to be drawn to the unit from as far away as 30 meters. SystemPlus incorporates a TVOC unit together with pump, sample preconditioning with flow cut off switch, optional USB data logger and power supply all contained in a waterproof housing.



Applications include:

- Manufacturing • Processing • Offshore • Refineries & petrochemical
- Chemical • Waste water treatment • Pulp & paper • Pharmaceutical
- Indoor air quality • Solvent recovery systems • Industrial painting & coating

TECHNICAL SPECIFICATION

SENSOR (PID)

10.6 eV lamp with Ion Science patented Fence Electrode Technology*

HAZARDOUS AREA SAFETY APPROVALS

ATEX: II 3 G Ex nA IIC T4 (-20°C ≤ Ta ≤ 50°C)

ATEX / IECEx: II 2 G Ex ia IIC T4 (-20°C ≤ Ta ≤ 50°C)

INGRESS PROTECTION RATING

Designed to IP65

Dependent on cable glands fitted sensor to IP53

POWER

5-28 VDC Max 65 mA

OUTPUT

4-20 mA requires a 8-35 VDC power supply

For IS requirements 8-30 VDC power supply

RANGE

0-10 ppm, 0-100 ppm, 0-1000 ppm (user selectable)

SAMPLING

Diffusion (can be pumped if required using an adaptor)

DISPLAY

7 segment, 4 digit LCD, 4 color LEDs

RESPONSE

Sensor - T90 < 5 sec**

ACCURACY

0-100 ppm : +/- 2% or +/- 1 ppm (whichever is greater)

100-1000 ppm: +/- 10% or +/- 10 ppm (whichever is greater)

LINEARITY

0-1000ppm > 75%

CALIBRATION

Magnetically accessed 100 ppm Isobutylene via calibration kit accessory

TEMPERATURE

Operating: -20 to 50 °C (-4 - 122 °F) Humidity: 0-95% RH

(non-condensing)

WEIGHT & DIMENSIONS

Instrument: 1.4 kg (3.1 lb) Packed: 1.6 kg (3.5 lb)

Dimensions: 181 x 125 x 76 mm (7.1 x 4.9 x 3")

4-20 mA ALARM LEVELS

Selectable 2 mA & 3.5 mA options

NB: All specifications are based upon isobutylene calibration at 20°C (68°F), up to 100 ppm at atmospheric pressure.

*The Fence Electrode technology referred to in this document is produced by Ion Science Ltd, and protected by patents. U.S. Patent No. 7,046,012. EP 1474681, other patents pending.

**TVOC has a variable duty cycle set to 1 minute as standard. The user can adjust this to between 5 seconds and 5 minutes. TVOC is a registered trademark of Ion Science Ltd.

Distributed by:



Ex-Ox-Tox Gasdetectie
Westerdreef 5V
2152 CS Nieuw-Vennep
Telefoon: 0252 620885
E-mail: info@exoxtox.nl
Website: www.exoxtox.nl

