

# SENSIT® GOLD G2 VERSATILE MULTIPLE GAS DETECTION INSTRUMENT

#### FIND GAS LEAKS FASTER

**SENSIT® GOLD G2** is the most versatile and user-friendly SENSIT available. The "G2" can be configured for combustible gas readings in PPM, LEL and/or percent volume, as well as a variety of toxic sensors and oxygen.

The **SENSIT GOLD G2** is ideal for leak location and confined space applications. This instrument can also be used for inert gas operations to detect combustible gases in oxygen-free environments.

#### **Displays Up To 4 Gases Simultaneously**

- LEL (%Volume and PPM Optional)
- Oxygen
- Carbon Monoxide
- Hydrogen Sulfide
- Hydrogen Cyanide (Optional)

#### Selectable Gas Type

- Methane (Natural Gas)
- Propane



#### **INDUSTRY USERS**

Gas Companies (natural & propane)
Gas Exploration & Transmission COs
Industrial Plants
Chemical/Petro Chemical Plants
Fire - Hazmat - Arson Services
HVAC Contractors



#### **APPLICATIONS**

Combustible Gas Leak Detection
Gas Leak Survey
Underground Leak Pinpointing
Carbon Monoxide Investigations
Confined Space Monitoring
Combustible Gas Measurements
Pipeline & Vessel Purging
Inert Gas Operations
Method 21 Emissions Testing

#### **G2 Standard Features**

- Internal Pump Fast Sampling
- Digital "Tick" Control Fast Leak Location
- Lowest Cost, Long Life Sensors
- LED Warning Lights
- Bright Graphic Display
- Loud Audible Alarm
- Battery Strength Indicator
- Internal Memory
- Exceptional Water Protection



#### PARTIAL LIST OF GASES SENSED\*

Butane

Carbon Monoxide

Gasoline

Hydrogen Sulfide

Methane

Natural Gas

Oxygen

Propane

<sup>\*</sup>Contact Sensit Technologies for more info.



SENSOR SPECI	FICATIONS RESOLUTION	RANGE	ACCURACY
PPM*	1ppm or 10ppm	0-10,000 ppm	±10%
LEL	0.1% up to 2%	0-100% LEL	±10%
% NAT GAS	0.1%	5-100% GAS	±5%
% PROPANE	0.1%	2.2-100% GAS	±5%
O2	0.1%	0-25%	±0.2% or 2%**
CO	1ppm	0-2000ppm	±5ppm or 5%**
H2S	1ppm	0-100ppm	±2ppm or 5%**
HCN	1ppm	0-30ppm	±1ppm or 5%**
*PPM Optional PPM Ranges Available: 0-2,000ppm, 0-5,000ppm, 0-10,000ppm  **Whichever is greater			

#### **PRODUCT SPECIFICATIONS**

Size:  $11.5'' \times 3'' \times 2.32'' (29.2 \times 7.6 \times 5.9 \text{ cm})$ 

Weight: 1.2 lb. (544 g)

Operational Temp: -4 to 104 F (-20 to 40° C)

Battery Life: Alkaline: Approximately 18 hrs. Continuous



#### STANDARD KIT

Wrist Strap Hard Carrying Case 3 "C" Batteries T10 Allen Wrench Extra Sensor Cap Instruction Manual Choice of 2 Piece Bar Hole Probe or Confined Space Probe

#### **OPTIONAL FEATURES**

#### **Data Logging Options:**

100 Instant Event Saves 1600 Auto Log Saves 100 Bar Hole Tests

#### **ADDITIONAL FEATURES**

#### **Bar Hole Test Features:**

Peak Readings Sustained Readings Timed Test

#### **Adjustable Calibration Reminders:**

Calibration Due Calibration Over-Due (Shows at Start-up)

#### **Adjustable Gas Scales:**

Auto Range Point for LEL to %Vol

#### **Gas Identification Alert Options:**

"NSR" - Non-Standard Response
"NSC" - Combustible Other Than Gas Calibrated

to (4-5% Volume)

ATEX Cert. No. TRAC11ATEX21304X

Ex ib IIB T3 AEx ia IIB T3 IP54

#### CERTIFICATE ISSUED BY:



Listed UL 913

Intrinsically Safe for Use in Class I, Groups C and D, T3 Hazardous Locations

## SENSIT GOLD G2 ACCESSORIES (LEL) (PPM\* + LEL)

SMART-CAL Auto Calibration Station Only Part #914-00000-01

SMART-Cal Standard Gas Kit 221 Liter (Not for use with H2S, Propane or 100% CH4) Part # 881-00045

Smart-Cal 58 liter H2S Cal Kit only Part # 881-00047

### Manual Calibration Kits are available. Please contact factory for price and part number.

21 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-080021

103 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-140001

221 liter Combo Gas (2.5% CH4/100ppm CO) Part # 315-180028

21 liter 1.1% Propane/Air Part # 315-080022

58 liter Hydrogen Sulfide (25ppm H2S/Air) Part # 315-120001

Sensor Cap (Replacement) w/"O" Rings Part # 870-00018

Extension Adapter Part # 870-00012

Hot Air Probe Part # 883-00023

Confined Space Probe Part # 883-00015

IR Link Part # 870-00039 Printer (Infrared) Part # 870-00004

Wrench (Battery Compartment Tool)
Part # 360-00105

# The following accessories to be used with the SENSIT GOLD G2 (LEL + % V/V) (PPM\* + LEL + % V/V)

21 liter 100% Methane Part # 315-080007

Demand Regulator – Use with Line Gas Part # 880-00007

2pc Probe Assembly Part # 883-00036

30" Brass Probe (5/16 OD) Part # 883-00018

32" Fiberglass Probe Part # 883-00019

Purge Probe (Brass) Part # 883-00030

Plunger Bar 42" Part # 870-00010

Hydrocarbon Filter Kit (6 pack) Part # 873-00015

Inline "Mini" Hydrocarbon Filter Kit (10 pack – BH probe with filter required) Part # 873-00012

\*PPM Optional



MADE IN USA

SENSIT Technologies is in compliance with ISO 9001:2008











Ex-Ox-Tox Gasdetectie Westerdreef 5V 2152 CS Nieuw-Vennep Telefoon: 0252 620885

Distributed by:

E-mail: info@exoxtox.nl Website: www.exoxtox.nl